



ADVANCED

Surveillance Solution

Qian POE IP Camera 5MP Bullet

CAPTURE EVERY DETAIL

The **2.8 mm fixed lens** offers a wide field of view, allowing you to cover more ground with fewer cameras. With a **maximum resolution of 5MP (2560x1920) at 20 frames per second**, you can expect high-quality footage with precise details, ensuring you don't miss any important information.





SECURITY WITH INTELLIGENT DETECTION

The **Qian POE IP Camera 5MP Bullet** goes beyond standard surveillance capabilities by **supporting intrusion and line-crossing detection based on human recognition**. This intelligent feature provides accurate detection of unauthorized access or movement, allowing you to proactively respond to potential threats.

SEE CLEARLY IN ANY LIGHTING

- **DWDR** (Digital Wide Dynamic Range)
- **3D DNR** (Digital Noise Reduction)
- **HLC** (Highlight Compensation)
- **BLC** (Backlight Compensation)
- Defog
- 5MP
- Night vision
- Range of up to 30 meters.

Whether it's a dimly lit room or an outdoor area, the **Qian POE IP Camera 5MP Bullet** ensures reliable monitoring in any lighting condition.



FLEXIBLE INSTALLATION & STORAGE

For convenient power options, the **Qian POE IP Camera 5MP Bullet** supports both **12V DC and Power over Ethernet (PoE)**, offering flexible installation choices to suit your specific needs. The **integrated Micro SD Card Slot** supports up to **256GB of storage**, eliminating the need for additional devices and ensuring ample space for storing recorded footage.





SHARPER VISION

The **Qian POE IP Camera 5MP Bullet** is equipped with a **1/3" progressive scan CMOS sensor**, offering superior image quality, smoother video capture, better low-light performance, and support for higher resolutions, making it an excellent choice for various surveillance and monitoring applications.

PROTECTION IN ANY WEATHER

Designed to withstand challenging environments, the **Qian POE IP Camera 5MP Bullet** has an **IP66 rating**, providing protection against dust and water. It is built to endure various weather conditions, making it suitable for both indoor and outdoor installations.





Qian P0E IP Camera 5MP Bullet **QEC-IBUL5**

Image Sensor	1/3" Progressive Scan CMOS
Maximum Resolution	2560(H)×1920(V)
Electronic shutter	Auto/Manual, 1/5 ~ 1/20,000s
Minimum Illumination	Color: 0.1 Lux @ (F1.6,AGC ON) B/W: 0 Lux @ (IR LED ON)
Signal to Noise Ratio S/N	55 dB
Day-Night Mode	Auto/ Day/ Night/ Timing
Wide Dynamic Range	DWDR
IR Range	Up to 30 m (98.4 ft)
IR On/Off Control	Auto/Manual
Pan/Tilt/Rotation Range	Pan: 0° ~ 360°, Tilt: 0° ~ 90° Rotation: 0° ~ 360°

Lens Type	Fixed focal
Iris	Fixed Iris
Focal length	2.8 mm
F Number	F 2.0
Angle of View	H: 93.2°, V: 50.2°
video compression code rate	H.264/ H.265/ H.265+[Smart Encode]
Streaming Capability	2 streams
Stream/Frame Rate	Main Stream: 2560×1920, 2560×1440, 2304×1296, 1920×1080, 1280×720, 704×576 @ 20fps Sub Stream: 640×360 @ 20fps
Bit Rate	CBR/VBR, Main Stream: 512kbps ~ 6144kbps, Sub Stream: 128kbps ~ 1536kbps
Image Adjustment	Brightness/Sharpness/Contrast/Saturation
White Balance	Auto/Manual
Support Features	Mirror, Motion Detection, Privacy Masking, Human Detection, Reset Button
Digital noise reduction	2D/3D NR
Image Enhancement	DWDR/HLC/BLC/Defog
Protocols	IPv4, RTSP/RTP/RTCP, TCP/UDP,DHCP, DNS, DDNS, UPNP, ICMP, IGMP, NTP, SMTP, 802.1x, SNMP, HTTP/HTTPS, PPPoE
Interoperability	ONVIF, SDK
Max. User Access	4 Users
Web Viewer	<IE11, Chrome, Firefox, Microsoft Edge
Management Software	InView Pro/ CMS
Smart Function	Intrusion and Line crossing detection based on human detection
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Operating and Storage Temperature	Storage
Storage	DC12V/POE (IEEE 802.3af)
Power Consumption	Max 5W
Operating temperature	-25°C ~ 55°C (-13°F ~ 131°F)
Operating humidity	Less than 90% RH
Ingress Protection	IP66
Certifications	CE/ FCC
Casing	Metal
Dimensions	181.9 × 66.26 × 66.17 mm (7.16 × 2.61 × 2.60 inch)
Net weight	0.35 kg (0.77 lb)
EAN	7500619011402